

PIERRE NATURELLE :MIXITÉ BOIS-PIERRE, CONSTRUCTION HORS SITEET RÉEMPLOI.

Bordeaux-11/06/2024





Where is my natural prefabricated stone structure !??



Pierre Debout, bois en travers soutiendra l'Univers.















Concept 'précontraint' - Pierre Noël - 1968

Précontraint.



Assembly prestressed stone beam - The Stonemasonry Company - 2022



























15 CLERKENWELL CLOSE




































Queens Building, Cambridge - 2000




15 Clerkenwell Close, London - 2017







- COMPARISON OF DIFFERENT MATERIALS -LOAD: 1000 kN - Length: 4m




mm

(kg coze)





Floors Lock Most of Embodied Carbon




47% up to

of carbon in modern buildings is embodied in floor planks due to the substantial volume of material required.




















Comparison of the construction-related embodied carbon values of Scenarios for Stone Tower


















5 Exploded Axonometric
Scale: 1:70































- Setting out
 Drill holes in conceret slab
 Mortar bed
 Temporary props



- Scafolding
 Install beam with thermal pad and M20 bolts

- Mortar bed
 Lower beams onto column heads
 Fosten RSA angles onto column nodes
 Mortar bed on RSA
 Lower floor plank










ZERO BETON
















CLT core, floor plate + glulam columns

- 1 Curtain wall
- 2 Cavity barrier
- 3 Two-way span CLT panel 4 CLT wall panel
- 5 Screed topping
- 6 Glulam column 7 Flooring joint 8 CLT stair



CLT core, floor plate + stone columns

9 Reinforced stone column



CLT floor plate + stone core, columns

- 10 Reinforced stone wall panel
- Pre-stressed stone landing
- 12 Protruding rebar13 RSA
- 14 Pre-stressed stone stair


9 Reinforced stone column

Stone grade: 2 Section: 350x350mm Axial capacity: 2000kN Building sequence:









CLT floor bears onto in steel column head

Steel column shoe fits into steel column head sandwiching CLT


Stone column levelled using

Finished floor level and carpet

11 Pre-stressed stone staircase

Stone grade: 2 Waist: 120mm Span: 2m Capacity: 3.5kN/m2 Building sequence:







A Steel top and bottom bracket fit onto slab rebate

Top and bottom bracket fixed to

Finished floor level and carpet fitted around stair top and bottom treads

10 Reinforced stone wall panel

Stone grade: 1 Thickness: 250mm Axial capacity: 3000kN/m Building sequence:








A Wall panel lowered onto protruding rebar

Wall panel levelled and grouted in position with temporary props

CLT floor panel supported by RSA and topping poured and cast around top and bottom of wall

























































Atelier Archiplein. Geneve











SINGLE WALL CLT FLOOR



SINGLE LOAD BEARING OUTSIDE WALL













Together We Are Solving a Big Problem at Scale Before 2030

- 1 Readily Available
- 2 -80% CO₂ emissions vs Conventional Concrete
- 3 No Sand + No Aggregate Extraction
- 4 No Finish + Very Low Lifecycle Cost
- 5 Reusable in Multiple Construction Cycles
- 6 No Need for Carbon Compensation

THE STRUCTURAL STONE COMPANY



THE STONEMASONRY COMPANY LIMITED $\longrightarrow \longrightarrow \longrightarrow$





























